Analogue Speed Dome Camera

Model: SC-13R501

Features

- OSD menu is available
- Keep original analog system
- AHD/TVI/CVI/CVBS selectable
- Real time transmission, lossless video
- Long distance transmission up to 300M
- 7” Total Metal Housing, IP66 rate protection

Specification

Model	SC-13R501	
Camera		
Output Pixels	1920 x 1080 /30fps ; 1920 x 1080 /25fps	
Lens	20x 4.7mm~94mm	36x 4.6mm~165mm
BLC	Support	
AGC	Auto/Manual	
WB	Indoor/Outdoor/Auto/Manual	
S/N Ratio	≥50dB	
D-WDR	Support	
Dome		
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°	
Rotation Speed	Pan: 0~200°/s, Tilt:0~100°/s	
Medium rotation speed (optional)	Pan: 0~80°/s, Tilt:0~40°/s	
Auto Flip	Horizontal 180°, Vertical 93°	
Preset Points	220pcs preset (Preset Dwell time 01-60s interval available)	
A-B Scan	User programmable (scan speed 1-64 levels setting available)	
Guard Tours	3 groups (Max.16 points, dwell time user selectable)	
PWR On Action	Memory/Pattern 1/Tour 1/360° scan/A-B scan/Park 1/None	
Park Mode	Pattern 1/Tour 1/360° scan/A-B scan/Park 1/None	
Park Time	1-60mins available	
Video interface output	AHD/TVI/CVI/CVBS selectable	
Communication mode	RS485 (+/-) / coaxial cable	
Operating Temperature	-40℃~+60℃	
Power	DC12V 4A / (AC24V 3A optional)	
Power Consumption	≤ 25W	
Lightning Protection	Transient voltage 6000V	
IR parameters		
Auto Control IR LED	PWM	
IR distance	Up to 120 meters	
IR LED	8PCS Array 42Mil IR LED	

Copyright © 2020 | All Rights Reserved By inkix. | Data Subject To Change Without Notice.|

www.inkix.hk