

4.5" High Speed Dome Camera

Model: SC-HD80F

- ▶ 4.5" full metal housing, IP66
- ▶ Support audio (optional)
- ▶ ONVIF2.4; Support P2P function
- ▶ Support H.264 (H.265)compression
- ▶ Pan/Tilt/Zoom, A-B scan, Tour available



Camera

Resolution	2MP	5MP
Sensor	HI3516E + Sony307	HI3516E + Sony335
Output pixel	1920x1080@20fps	2560x1920@20fps
Lens	10X f=5.1~51mm	10X f=5.1~51mm
BLC	Support	
AGC	Auto/manual	
WB	Auto/manual/indoor/outdoor	
DNR	2DNR,3DNR	
WDR	DWDR	
S/N Ratio	≥50dB	

Dome

Communications Protocol	HTTP,TCP/IP,IPv4,UPNP,RSTP,UDP,SMTP,NTP,HDCP,DNS,PPPOE,DDNS,FTP
Software Control	IE, EasyVMS, Management Platform, P2P
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Rotation Speed	Pan: 0~200°/s , Tilt:0~100°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmabel (scan speed 1-64 levels setting available)
Guard Tours	3 groups (max.16 points, dwell time user selectable)
AB scan range	Any point in range: 0°~360°
AB scan speed	1-9 grades
Operating temperature	-40°~+60°C
Operation menu	English
Power	DC12V 3A (AC24V 2A optional)
Consumption	≤15W
IR distance	Up to 60 meters
LEDs	6PCS IR LED